

SAFETY DATA SHEET

HARDWAX FLOOR OIL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

▼ Trade name

HARDWAX FLOOR OIL

▼ Unique formula identifier (UFI)

7UH1-A0QA-800P-9YED

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Oil treatment of wood.

▼ Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Junckers Industrier A/S

Vaerftsvej 4

4600 Koege

Denmark

Tel. +45 70 80 30 00

▼ Importer

Junckers Ltd.

5 Warren Yard, Warren Park, Stratford Road, Wolverton Mill

MK12 5NW Milton Keynes, Buckinghamshire

Tel. 0 1376 534 700

E-mail

productsafety@junckers.dk

Revision

17/03/2023

SDS Version

2.0

Date of previous version

31/05/2022 (1.0)

1.4. Emergency telephone number

National Poisons Information Service (NPIS): Call 111 (24 h service).

See section 4 for first aid measures.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

2.2. Label elements

Hazard pictogram(s)



Signal word

Warning

Hazard statement(s)

Flammable liquid and vapour. (H226)

Safety statement(s)

General

Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Keep container tightly closed. (P233)

Response

-

Storage

-

▼ Disposal

Dispose of contents/container in accordance with local regulation. (P501)

▼ Hazardous substances

None known.

▼ Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.
EUH208, Contains Phthalic anhydride. May produce an allergic reaction.
UFI: 7UH1-A0QA-800P-9YED

▼ VOC

VOC content: ≤ 500 g/L
MAXIMUM VOC CONTENT (Phase II, category A/i (SB): 500 g/L)

2.3. Other hazards

▼ Additional warnings

Cloths etc. used to apply the product can self-ignite. Place used cloths in an airtight and non-flammable container (e.g. a jam jar or a metal can with a lid). Dispose of in accordance with national waste regulations.
This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. ▼ Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, < 2 % aromatics	CAS No.: EC No.: 940-727-9 UK-REACH: Index No.:	25-35%	EUH066 Asp. Tox. 1, H304	
Hydrocarbons, C11-C12, isoalkanes, < 2 % aromatics	CAS No.: EC No.: 918-167-1 UK-REACH: Index No.:	10-15%	EUH066 Flam. Liq. 3, H226 Asp. Tox. 1, H304	
Hydrocarbons, C11-C13, isoalkanes, < 2 % aromatics	CAS No.: EC No.: 920-901-0 UK-REACH: Index No.:	5-10%	EUH066 Asp. Tox. 1, H304	
Hydrocarbons, C11-C14, isoalkanes, cyclics, < 2 % aromatics	CAS No.: 1174522-15-6 EC No.: 927-285-2 UK-REACH: Index No.:	5-10%	EUH066 Asp. Tox. 1, H304	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	CAS No.: EC No.: 918-481-9 UK-REACH: Index No.:	1-3%	EUH066 Asp. Tox. 1, H304	
Phthalic anhydride	CAS No.: 85-44-9 EC No.: 201-607-5 UK-REACH: Index No.: 607-009-00-4	<0,2%	Acute Tox. 4, H302 (ATE: 1530.00 mg/kg) Skin Irrit. 2, H315 Skin Sens. 1, H317	

Eye Dam. 1, H318
Resp. Sens. 1, H334
STOT SE 3, H335

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

▼ Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

▼ General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

▼ Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. ▼ Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may produce an allergic reaction through inhalation. The allergic reaction typically takes place within an hour after exposure. The reaction results in an inflammatory reaction to the lungs.

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. ▼ Indication of any immediate medical attention and special treatment needed

None known.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. ▼ Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact

The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.
Hazchem Code: ●3Y

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

6.2. ▼ Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. ▼ Methods and material for containment and cleaning up

Use sand, sawdust, soil, vermiculite or similar to collect liquid material. Subsequently, place in a suitable waste container.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Cloths etc. used to apply the product can self-ignite. Place used cloths in an airtight and non-flammable container.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. ▼ Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

▼ Storage temperature

No specific requirements

▼ Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, < 2 % aromatics

Long term exposure limit (8 hours) (mg/m³): 1000 (RCP)

Hydrocarbons, C11-C12, isoalkanes, < 2 % aromatics

Long term exposure limit (8 hours) (mg/m³): 1000 (RCP)

Hydrocarbons, C11-C13, isoalkanes, < 2 % aromatics

Long term exposure limit (8 hours) (mg/m³): 1000 (RCP)

Hydrocarbons, C11-C14, isoalkanes, cyclics, < 2 % aromatics

Long term exposure limit (8 hours) (mg/m³): 1000 (RCP)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Long term exposure limit (8 hours) (mg/m³): 1000 (RCP)

Phthalic anhydride

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Long term exposure limit (8 hours) (mg/m³): 4
 Short term exposure limit (15 minutes) (mg/m³): 12
 Annotations:
 Sen = Capable of causing occupational asthma.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
 EH40/2005 Workplace exposure limits (Fourth Edition 2020).

RCP limit values for hydrocarbons from Hydrocarbon Solvents Producers Association, HCS key data, 23.07.2018.

▼ DNEL

Phthalic anhydride

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	14 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	8,7 mg/m ³
Long term – Systemic effects - Workers	Inhalation	49,4 mg/m ³
Long term – Systemic effects - General population	Oral	5 mg/kg bw/day
Short term – Systemic effects - General population	Oral	25 mg/kg bw/day

▼ PNEC

Phthalic anhydride

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1 mg/l
Freshwater sediment		3,8 mg/kg dw
Intermittent release (freshwater)		5,6 mg/l
Marine water		0,1 mg/l
Marine water sediment		0,38 mg/kg dw
Sewage treatment plant		10 mg/l
Soil		0,173 mg/kg dw

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼ Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Work situation	Type	Class	Colour	Standards
In case of insufficient ventilation	Gas filter A	2 (medium capacity)	Brown	EN14387



Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn	-	-



Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0,4	> 480	EN374-2, EN374-3, EN388



Eye protection

Type	Standards
Safety glasses with side shields	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Light brown

Odour / Odour threshold

Hydrocarbons

pH

Testing not relevant or not possible due to the nature of the product.

▼ Density (g/cm³)

0,88

Kinematic viscosity

> 20,5 mm²/s (40 °C)

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

59

▼ Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

VOC (g/l)

≤ 500

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. ▼ Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. ▼ Possibility of hazardous reactions

None known.

10.4. ▼ Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. ▼ Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

▼ Acute toxicity

Product/substance	Phthalic anhydride
Species:	Rat, Wistar, male
Route of exposure:	Oral
Test:	LD50
Result:	1530 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

▼ Long term effects

None known.

▼ Endocrine disrupting properties

Not applicable.

▼ Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

No data available.

12.2. ▼ Persistence and degradability

Product/substance	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, < 2 % aromatics
Biodegradable:	Yes
Test method:	OECD 301 F
Result:	71 %

Product/substance	Hydrocarbons, C11-C14, isoalkanes, cyclics, < 2 % aromatics
Biodegradable:	Yes
Test method:	OECD 301 F
Result:	77,6 %

Product/substance	Phthalic anhydride
Biodegradable:	Yes
Test method:	OECD 301 C
Result:	85 %

12.3. ▼ Bioaccumulative potential

Product/substance	Phthalic anhydride
Test method:	
Potential bioaccumulation:	No
LogPow:	1,6
BCF:	5,3
Other information:	

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. ▼ Endocrine disrupting properties

Not applicable.

12.7. ▼ Other adverse effects

None known.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances




Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1263	PAINT	Class: 3 Labels: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1263	PAINT	Class: 3 Labels: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1263	PAINT	Class: 3 Labels: 3 Classification code: F1 	III	No	See below for additional information.

* Packing group

** Environmental hazards

▼ Additional information

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: ●3Y

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

No special.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

Additional information

Not applicable.

▼ Sources

Control of Major Accident Hazards (COMAH) Regulations 2015.
2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H318, Causes serious eye damage.
H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335, May cause respiratory irritation.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH = CLP-specific hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of classification and labelling of chemicals
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = Logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = Specific Concentration Limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time Weighted Average
UN = United Nations
UVCB = Substances of Unknown or Variable composition, Complex reaction products or Biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and very Bioaccumulative

Additional information

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

The classification of the mixture in regard to physical hazards has been based on experimental data.

▼ The safety data sheet is validated by

ULS

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en